

1033234 | 90° HSS countersinker - Hexagonal shank TECHNIC (Plastic sleeve)

Fast and strong countersinking bit for steels. Suitable for Shock Series screwdrivers and machines 6.35 hexagonal shank.




- Especially for steels and aluminiums
- Tough
- Flooding of the screw heads
- Post-drill deburring
- Quick tool changing
- 90° milling angle
- 6.35 mm hexagonal shank
- High-speed steel
- Head with 3 cutting edges

Machine



Application



Features



Properties and benefits

- + 90° milling angle : For 90° chamfering operation. ➡ For making 90° chamfering to down screw and/or rivet heads.
- + 6.35 mm hexagonal shank / DIN 3126 C 6.3 standard: geometric characteristics comply with dimensional standards. ➡ Enables a perfect hold with bit-holders.
- + High-speed steel: HSS substrate ➡ For general use in steels and cast irons up to 950 N/mm²
- + Head with 3 cutting edges: tool geometry designed with 3 cutting edges. ➡ Enables the excellent distribution of the cutting force and a neat surface condition.

Sets



5f pieces - 4 90° hex shank HSS countersinker Ø 8,3 to 16.5 mm + 1 bit-holder
7 pieces - 6 90° hexagonal shank HSS countersinker Ø 6.3 to 20.5 mm + 1 bit-holder

| Item number M3 | EAN (13 digits) | M3 | Cutter diameter | Handle diameter or CM | Drill diameter d3 | Total length | Trimmed length |
|----------------|-----------------|----|-----------------|-----------------------|-------------------|--------------|----------------|
| 10332340630 | 3221910881917 | | 6,3 | 6.35 | 1.5 | 31 | |
| 10332340830 | 3221910881924 | | 8,3 | 6.35 | 2 | 31 | |
| 10332341040 | 3221910881931 | | 10,4 | 6.35 | 2.5 | 35 | |
| 10332341240 | 3221910881948 | | 12,4 | 6.35 | 2.8 | 35 | |
| 10332341650 | 3221910881955 | | 16,5 | 6.35 | 3.2 | 40 | |
| 10332342050 | 3221910881962 | | 20,5 | 6.35 | 3.5 | 40 | |