

Drill bit crown made of tempered steel with asymmetrical carbide teeth.
Aggressive drilling of hard materials.



- SDSmax shank
- High-temp. soldering

Machine



Application



Concrete Stone

Features



Properties and benefits

- + SDSmax shank: attachment for SDSmax hammer drills (18 mm shank diameter) compliant with the SDSmax label, greater than 3 joules. ➡ Maximum striking power transmission for the simple and fast processing of the most difficult materials. For bits larger than 12 mm.
- + High-temperature soldering: the carbide teeth are welded at a high temperature for better adherence to the crown. ➡ The procedure for the fixing of the pads increases the service life of the tool.

Related products



CK annular bit holder TECHNIC (Plastic sleeve)



CK drill drift ESSENTIAL (Plastic sleeve)



Drill bit - annular bit pilot ESSENTIAL (Plastic sleeve)

Code	EAN	Ø	Blade height	QTY
10907543000	3221910863951	30	100	1
10907543500	3221910863968	35	100	1
10907544000	3221910863975	40	100	1
10907544500	3221910863982	45	100	1
10907545000	3221910863999	50	100	1
10907546000	3221910864002	60	100	1
10907546600	3221910864729	66	100	1
10907547000	3221910864026	70	100	1
10907548000	3221910864033	80	100	1
10907549000	3221910864040	90	100	1
109075410000	3221910863920	100	100	1
109075411000	3221910863937	110	100	1
109075412500	3221910863944	125	100	1