

11452070002 | 26 pieces - 25 fully ground HSS metal drill bit - Split point Ø 2 to 13 mm + 1 HSS countersinker Ø 16.5 mm

Drill bit for the drilling of steels and cast irons, thanks to its self-centring sharpening.



- Especially for steels and aluminiums
- Rapid drilling
- Versatile use
- Automatic centring
- Cylindrical shank
- 30° type N flute
- High-speed steel
- 118° tip

25 metal drill bits Ø 2 - 2.5 - 3 - 3.3 - 3.5 - 4 - 4 - 4.2 - 4.5 - 5 - 5 - 5 - 5.5 - 6 - 6.5 - 6.8 - 7 - 7.5 - 8 - 8.5 - 9 - 10 - 11 - 12 - 13 mm + 1 countersinking bit Ø 16,5mm - RANGER Case





Machine









Application











Features























Properties and benefits

- Split-point grinding:reduction of the drill tip. Denables the simple self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the requried axial load.
- Cylindrical shank: the diameter of the shank is equal to the diameter of the tip. 2 Enables versatile use on portable electrical tools and CNC machine tools.
- 30° type N flute: normal flute profile with a 30° helix angle. Suitable for general use. Provides good rigidity to the tool, as well as excellent drilling precision.
- High-speed steel: HSS substrate For general use in steels and cast irons up to 950 N/mm²
- 118° tip: 118° tip angle for the sharpening of the drill bit. Suitable for general use in materials with long shavings. Enables the rapid attach of the material and simple centring.

Données de gestion :

PCB: 1 / Kilogram.: 0,930 / Dimensions: 0205x0135x0050 mm / EAN: 3221912205179