

XT51022 | Reciprocating saw blade - Multi-directional - For wood, MDF, wood with nails, metal, composite materials, Epoxy - Universal double attachment **TECHNIC** (Carton sleeve)

Cutting of soft wood, construction wood, MDF, wood with embedded nails, metal, steel, reinforced plastics, epoxy. The toothing at the end of the blade enables plunge cutting in wood.



- **Maximum long life**
- **X2 universal attachment**
- **8% cobalt steel toothing**
- **Toothed tip**



Machine



Application



Sheet metal

Features



Properties and benefits

- + Double universal attachment: enables the insertion of the blades into the machine either way round. ➡ Enables the use of either side of the cutting edge of the blade, without changing the blade. Also enables cutting when ascending or descending.
- + Bi-metal cobalt 8%: combination of teeth made from quick-cutting tempered steel (HSS) enriched with cobalt, and the the body made from HCS. ➡ These blades offer high strength, versatility, and durability. Ideal for intensive work, in the strongest of materials.
- + Toothed tip: presence of teeth on the outside of the tip of the blade. ➡ Enable plunge cutting into wood.



Code	EAN	Cutting thickness	Cutting type	Sawing cutting quality	L	I	Pitch	QTY	PCB
XT505820109 3221912213815			Straight cut	Finishing Quick Cut	150	130	4.2 (back 2.5)	2	1