

## XT51082 | For wood, MDF, nail-embedded wood, metal -**Universal double shank TECHNIC (Carton sleeve)**

Cutting of soft wood, construction wood, MDF, wood with embedded nails, metal sheet, metal tubing. The toothing at the end of the blade enables plunge cutting in wood.

	<ul> <li>Maximum long life</li> <li>X2 universal attachment</li> <li>Milled, wavy set</li> <li>8% cobalt steel toothing</li> </ul>		BOIS MÉTAL Wood Metal	BOIS
Machine	Application			
	Hard wood Sheet metal	Wood with nails		
Features				
Properties and benefits				
<ul> <li>Double universal attac cutting edge of the bla</li> </ul>	chment: enables the insertion of the ade, without changing the blade. Als	blades into the machine ei sop enables cutting when a	ther way round.	Enables the use of either side of the condition of the co

- Milled, wavy set: the milled wavy toothing maintains a contact surface between the blade and the material. O Prevents jolts and enables very clean cuts into plywood, aluminium, non-ferrous metals and plastic materials.
- Bi-metal cobalt 8%: combination of teeth made from quick-cutting tempered steel (HSS) enriched with cobalt, and the the body made from HCS. SThese blades offer high strength, versatility, and durability. Ideal for intensive work, in the strongest of materials.



	Code	EAN	Cutting thickness	Cutting type	Sawing cutting quality	L	Ι	Pitch	QTY	PCB
XT5058201103221912213822			Straight cut	Finishing Quick Cut	150	130	2.5 (back 1.8)	2	1	