

Tool made of bi-metal HSS steel Ideal for routing pipes, ducts. Speed and precision thanks to the variable pitch teeth.




- Hexagonal shank
- Alternate top bevel
- HSS toothing
- Variable teeth
- All-in-one



Machine



Application



Features



Properties and benefits

- + Hexagonal shank: shank machined with 6 flats ➡ Excellent hold of the bit inside the chuck, enables maximum torque transmission.
- + Alternating teeth: teeth spaces alternating from left to right. ➡ Facilitates the cutting and removal of particles and prevents the blockage of the saw during cutting.
- + Bi-metal steel blade: combination of progressive toothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS). ➡ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.
- + Variable toothing: design whereby the teeth are positioned with irregular gaps (pitches) and with alternating small and large teeth with different gap sizes. ➡ Enables the cutting of a wide range of different materials. Reduces the risk of teeth breaking and reduces vibrations when cutting.
- + All-in-one: a complete tool including the base, m blade, and guide bit. ➡ A complete, ready-to-use tool.

Related products



70% biodegradable
cutting oil TECHNIC
(Blister Box)

| Code | EAN | Ø | Blade height | QTY | PCB |
|-------------|---------------|----|--------------|-----|-----|
| XT505220040 | 3221912164186 | 22 | 38 | 1 | 1 |
| XT505220041 | 3221912164179 | 29 | 38 | 1 | 1 |
| XT505220042 | 3221912164162 | 35 | 38 | 1 | 1 |
| XT505220043 | 3221912164148 | 44 | 38 | 1 | 1 |
| XT505220044 | 3221912164131 | 53 | 38 | 1 | 1 |
| XT505220045 | 3221912164124 | 68 | 38 | 1 | 1 |
| XT505220046 | 3221912164117 | 73 | 38 | 1 | 1 |
| XT505220047 | 3221912164094 | 83 | 38 | 1 | 1 |