

Tool made of bi-metal HSS steel Ideal for routing pipes, ducts. Speed and precision thanks to the variable pitch teeth.




- SDS+ attachment
- Alternate top bevel
- HSS toothing
- Variable teeth

Machine



Application



Features



Properties and benefits

- + SDS+ attachment: attachment for SDS+ hammer drills (10 mm shank diameter) compliant with the SDS+ label, up to a power of 3 joules.
 - ➡ Maximum striking power transmission for the simple and fast processing of the most difficult materials.
- + Alternating teeth: teeth spaces alternating from left to right.
 - ➡ Facilitates the cutting and removal of particles and prevents the blockage of the saw during cutting.
- + Bi-metal steel blade: combination of progressive toothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS).
 - ➡ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.
- + Variable toothing: design whereby the teeth are positioned with irregular gaps (pitches) and with alternating small and large teeth with different gap sizes.
 - ➡ Enables the cutting of a wide range of different materials. Reduces the risk of teeth breaking and reduces vibrations when cutting.

Related products



70% biodegradable
cutting oil TECHNIC
(Blister Box)

| Code | EAN | Ø | Blade height | QTY | PCB |
|---------------|---------------|----|--------------|-----|-----|
| XT505220060 | 3221912164087 | 35 | 38 | 1 | 1 |
| XT50522052229 | 3128820522292 | 65 | 38 | 1 | 1 |
| XT50522052233 | 3128820522339 | 67 | 38 | 1 | 1 |