

Tool made of bi-metal HSS steel Ideal for routing pipes, ducts. Speed and precision thanks to the variable pitch teeth.




- SDS+ attachment
- Alternate top bevel
- HSS toothing
- Variable teeth

#### Machine



#### Application



#### Features



#### Properties and benefits

- + SDS+ attachment: attachment for SDS+ hammer drills (10 mm shank diameter) compliant with the SDS+ label, up to a power of 3 joules.
  - ➡ Maximum striking power transmission for the simple and fast processing of the most difficult materials.
- + Alternating teeth: teeth spaces alternating from left to right. ➡ Facilitates the cutting and removal of particles and prevents the blockage of the saw during cutting.
- + Bi-metal steel blade: combination of progressive toothing made from quick-cutting tempered steel (HSS), and the body made from high-strength carbon steel (HCS). ➡ Very flexible, used when there is a risk that the attachment will break. Very high resistance to wear, for a longer service life.
- + Variable toothing: design whereby the teeth are positioned with irregular gaps (pitches) and with alternating small and large teeth with different gap sizes. ➡ Enables the cutting of a wide range of different materials. Reduces the risk of teeth breaking and reduces vibrations when cutting.

#### Related products



70% biodegradable  
cutting oil TECHNIC  
(Blister Box)

Code	EAN	Ø	Blade height	QTY
XT505220060	3221912164087	35	38	1
XT50522052229	3128820522292	65	38	1
XT50522052233	3128820522339	67	38	1